



SuperTimer II
www.supertimer.com
800-654-2088

SuperTimer II Packing List

Users Manual and other files on CD

SuperTimer II electronic assembly (white box/yellow label)

Speaker with cable

Power Supply (15VDC, 1Amp, 3.5mm, center positive)

50' RJ-11 silver cable (SuperTimer II to start gate board)

3.5' RJ-45 silver WIDE cable (timer to finish line board NOT CAT5!)

Please do not change any wires without calling us.

Electronics pack with:

Finish Circuit Board (orange/green connectors)

Start Solenoid Board with

Ready Micro-Switch (red/green wires unpolarized)

Magnetic Start Switch (white wires with tie wrap for mounting)

Magnet (round silver bar)

Blue plastic latch peg

Tie Wrap (for routing ready/start switch wires if needed)

2 each 6-32 x 3 screws (mount timer)

2 each 6-32 wing nuts (mount timer)

2 each #4 x 3/4 screws (mount ready switch)

6 each #4 x 1/2 screws (mount mag sensor, tie wrap and circuit boards)

Finish sensor pack with (per lane ordered):

Wired MSI Sensor (red/black wires)

Wired Red Led (red/blue wires)

Red Led Lens

Thin washer (for led lens)

Tie Wrap (for wire routing if needed)

#4 x 1/2 screw (mount tie wrap)

RaceManager Software Option for SuperTimer II includes (if purchased)

50' RJ-11 to DB-9 cable (SuperTimer II to computer serial port)

CD with software Manuals and RaceManager software

USB-Serial Adapter Option for RaceManager (if purchased)

(note: adapter driver software must be installed from CD)

Note: All cables are 'telephone standard' with the handle of the connector on the same side of the wire on both ends of the cable.

SuperTimer II Parts List Rev 10/15